

1

- Advantage / benefit:..... **Operating pressure up to max. 40 bar, corresponds to more than double the operating pressure in comparison with the common claw couplings according to system GEKA®**
- Material:..... Brass CW617N
- Claw distance:..... Uniformly 40 mm. Combinations with each other possible compatible with all other GEKA® versions
- Vacuum resistance:..... Up to 10 m water column (WC)
- Temperature range:..... Approx. -5 °C to +100 °C (depending on the quality of the sealing ring)
- Sealing:..... Standard with **GEKA® plus high-performance shaped sealing rings form 300 NBR (300C), patented**, temperature range from approx. -10 °C to +90 °C
- Options:..... Upon request GEKA® plus high-performance shaped sealing rings form 300, patented, in the qualities EPDM (300EPDM) and FKM (Fluororubber) according to DIN ISO 1629 (300V) as well as dirt strainers available for self-assembly
- Area of application:..... For water, industrial, suction and pressure hoses

The original



GEKA® plus hose pieces

Grommet with striking and hose protecting ribbed thread guarantees fixed hose fit. For integration of clamp and ferrule

Hose ID mm	10	13	16	19	25	32	38
Hose size	3/8"	1/2"	5/8"	3/4"	1"	1 1/4"	1 1/2"
PU units	10	10	10	10	10	10	10
Covering box units	160	150	160	120	100	100	60
Catalogue no.	40100	40101	40102	40103	40104	40106	40107
Item no.	04.0100	04.0101	04.0102	04.0103	04.0104	04.0106	04.0107

The original



GEKA® plus threaded parts with female thread

Flat seal ring NBR at the threaded side

Female thread mm	11,89	15,39	19,17	24,66	30,93	39,59	45,48
Female thread	G1/4	G3/8	G1/2	G3/4	G1	G1 1/4	G1 1/2
PU units	10	10	10	10	10	10	10
Covering box units	240	150	160	160	140	100	90
Catalogue no.	40108	40109	40110	40111	40113	40114	40116
Item no.	04.1108	04.1109	04.1110	04.1111	04.1113	04.1114	04.1116

The original



GEKA® plus threaded parts with male thread

Male thread mm	13,16	16,66	20,95	26,44	33,25	41,91	47,80
Male thread	G1/4	G3/8	G1/2	G3/4	G1	G1 1/4	G1 1/2
PU units	10	10	10	10	10	10	10
Covering box units	170	180	180	170	160	130	110
Catalogue no.	40119	40109A	40110A	40111A	40113A	40114A	40116A
Item no.	04.2119	04.2109	04.2110	04.2111	04.2113	04.2114	04.2116

The original



GEKA® plus dummy coupling

With bore for fixing of little chains

PU units	10
Covering box units	240
Catalogue no.	40118
Item no.	04.3118

GEKA® plus little chain

Material:..... Steel galvanised

For all GEKA® plus dummy couplings with bore



Length approx. mm	270
PU units	25
Catalogue no.	6620
Item no.	61.6620