

Silicone Radiator Hoses & Variforms

-50°C to +190°C

Product Details:

- Multi-ply silicone rubber reinforced with polyester.
- Smooth outer finish with liner of silicone rubber for zero leakage.
- Excellent ageing properties

Options:

- up to +250 °C resistant, wide range of colours.
- FR versions

Inside Diameter (mm)	Weight (kg/m)	Working Pressure (bar)	Burst Pressure (bar)
6.4	0.14	6.4	34
8	0.17	6.4	33
9.5	0.28	6.3	32
12.7	0.27	6	30
16	0.34	5.5	26
19	0.4	5	24.1
22	0.46	4.5	22.4
25	0.53	4.1	21.1
28	0.59	3.8	20.2
30	0.63	3.7	19.8
32	0.67	3.6	19.6
35	0.74	3.4	19
38	0.8	3.2	18
41	0.86	3.1	17.1
42	0.87	3	16.6
45	0.95	2.8	14.9
48	1.01	2.7	14.2
51	1.07	2.5	13.8
54	1.14	2.4	13.2
57	1.2	2.4	12.6
63	1.32	2.2	11
65	1.37	2.2	11
68	1.44	2.2	10.4
70	1.48	2.1	10
76	1.61	2	9.3
80	1.67	1.9	9
85	1.82	1.8	8.3
90	1.88	1.7	8

Other diameters: 26, 28, 40, 42, 45, 50, 52, 55, 58, 60, 62, 65, 67, 72, 80, 90, 91, 92, 100, 106, 110, 125, 130, 148, 150, 155, 156, 165, 180, 200, 210, 216

Other lengths spliced: 5 - 60 coils