



Fabryka Taśm Transporterowych
WOLBROM S.A.
 32-340 Wolbrom, ul. 1 Maja 100
 tel. (32) 649-71-00, 649-71-71, fax. (32) 649-71-01

FTT WOLBROM®

CERTIFICATE OF QUALITY 1210/1211

1. Rubber fabric conveyor belt **500 EP 500/3 4+2 T150** according **WT-13/13**

Belt number: **1210/1211**

2. Dimensions and physical parameters of belt

Requirements	Unit	Required	Obtained
Belt width	[mm]	500	505
Operating cover thickness	[mm]	4,0	4,2
Non operating cover thickness	[mm]	2,0	2,2
Tensile strength	[kN/m]	500	609
Elongation at load of 10% of nominal strength max.	[%]	1,5	0,7
Separation resistance min. [kN/m]			
- between the fabric plies		min.4,5	15,0
- of rubber covers form the core		min.3,5	10,85
Separation resistance change after ageing 125°C x 72h			
- between the fabric plies min.	[N/mm]	±30	-22,3
- rubber covers from the core min.	[N/mm]	±50	-5,9
Electric resistance max	[Ω]	3.0x10 ⁸	3,44*10 ⁷

Signature and stamp of
 Quality Control
 Specjalista d/s jakości


 Marcin Mosurek