

Tlaková hadice, 2P1 AA EVOLUTION PLUS, na vodu a vzduch,
čtvercově členěný obal, vysoce flexibilní, 10bar/-1bar, -
30°C/+80°C, CR/CR, černá

// 2P1AA



EVOLUTION PLUS

**Water-slurry S&D 10 bar (150 psi) - Square
corrugated - Extra flexible**

Tube: black synthetic rubber.

Reinforcement: high tensile textile cords with embedded steel helix wire.

Cover: black synthetic rubber, abrasion and ozone resistant.

Application: water suction and delivery. Special construction for maximum flexibility for slurry tankers.

Constant operation: -30 °C +80 °C (-22 °F +176 °F)

												
mm	in	mm	in	bar	psi	bar	psi	mm	in	%	kg/m	lb/ft
51,0	2"	65,00	2,56	10	150	30	450	51	2,01	100	1,440	0,97
76,0	3"	91,00	3,58	10	150	30	450	152	5,98	90	2,490	1,67
102,0	4"	119,00	4,69	10	150	30	450	204	8,03	90	3,510	2,36
152,0	6"	169,00	6,65	10	150	25	375	456	17,95	80	6,430	4,32
203,0	8"	222,00	8,74	10	150	25	375	812	31,97	70	11,040	7,42