










JAMAICA M

915098



Flexible layflat PVC hose, with polyester yarn reinforcement, resistant to elongation, for pressurized delivery of liquids in general.

DETAILS

	SMOOTH SURFACE	*****
	FLEXIBILITY	*
	ABRASION RESISTANCE	***
	TEMPERATURE RANGE	-5 °C 60 °C
	CHEMICAL RESISTANCE	PVC Table
	CRUSHING RESISTANCE	*
	MICROORGANISMS RESISTANCE	*****

Ø nominal mm	Ø nominal inch	Ø i.d. mm	Ø o.d. mm	working pressure at 23 °C bar	working press. at 40 °C bar	working press. at 60 °C bar	bursting press. at 23 °C bar	total thickness mm	weight meter g/m	# wires for angle n° x a°	working resistance kg	tensile breaking load kg	coil length m	Availability
51	2	51	55	5.5	4	2	17	2	410	36x75°	250	575	50/100	In stock
60		60	65	6	4.5	2.5	18	2.5	550	48x78°	450	1055	50/100	In stock
63	2 1/2	63.5	68.5	6	4.5	2.5	18	2.5	570	48x78°	480	1115	50/100	In stock
70		70	75	6	4.5	2.5	18	2.5	650	48x78°	535	1245	50/100	In stock
76	3	76	81	6	4.5	2.5	18	2.5	710	60x75°	600	1390	50/100	In stock
80		80	85	6	4.5	2.5	18	2.5	750	60x76°	620	1440	50/100	In stock
90	3 1/2	90	95	6	4.5	2.5	18	2.5	860	60x80°	700	1630	50/100	In stock
102	4	102	107	5	3	2	15	3	1000	72x78°	785	1825	50/100	In stock
110		110	116	5	3	2	15	3	1150	72x80°	865	2015	50/100	In stock
127	5	127	133	5	3	2	15	3	1350	72x80°	970	2255	50/100	In stock
152	6	152	158	4	3	1	12	3	1600	72x80°	1080	2520	50/100	In stock
204	8	204	210	1.5	1	0.5	5	3	2400	120x78°	1495	3480	50	In stock

All technical specifications apply to a temperature of 23° C ± 2° C (ISO 291)

The tolerance on all specifications ±5% (Tolerance Percentage is applicable on ALL DATA across our range)